

EC TYPE EXAMINATION (MODULE B) CERTIFICATE No. MED171319WS

This is to certify that RINA Services S.p.A. (Notified Body No. 0474) did undertake the relevant type approval procedures for the equipment identified below, which was found to be in compliance with the Life-Saving appliances requirements of Marine Equipment Directive (MED) 2014/90/EU, including the requirements and testing standards of Regulation (EU) 2018/773.

MED Item No

MED/1.2b

USCG Category Nº

161.110

Description

Position-indicating lights for life-saving appliances: (b) for

lifebuoys

Type

SM-3

Applicant

ACR ELECTRONICS, INC.

5757 RAVENSWOOD ROAD FORT LAUDERDALE 33312

U.S.A.

Testing standards

IMO Res.MSC.81(70), as amended

Reference standards

SOLAS 74 Reg.III/7, SOLAS 74 Reg.III/22, SOLAS 74 Reg.III/32, SOLAS

74 Reg.III/34, IMO Res.MSC.36(63)-(1994 HSC Code) 8, IMO

Res.MSC.48(66)-(LSA Code) I, IMO Res.MSC.48(66)-(LSA Code) II, IMO

Res.MSC.97(73)-(2000 HSC Code) 8.

Issued in SHANGHAI on

August 26, 2019

This Certificate is valid until

June 9, 2024

This Certificate consists of this sheet plus an attachment

RIJA

Hai Wen Zhang

RINA Services S.p.A.



ATTACHMENT TO CERTIFICATE No. MED171319WS Page 1 of 2

Manufacturer

XIAMEN LONAKO INDUSTRY & TRADE CO., LTD

Place of Manufacturer
N307
WEIYE BUILDING
CHINA PIONEERING PARK FOR CHINESE OVERSEAS SCHOLARS
XIAMEN
CHINA

Name & place of Authorised Representative Mr. Johannes Graf Strachwitz Walhallastraße 38, 80639 München, Germany GERMANY

Product Description

Model of Light: SM-3 - Lifebuoy light upright self-igniting.

The above light is manufactured with following characteristics:

Dimensions of main body: 9.9" (56 mm) Diameter;
 2.2" (253 mm) Height.

• Color of upper shell : Transparent

Color of Body: Orange

Total Weight: Light excluding batteries and bracket - 0.66 lbs (300 g);

Light including batteries (excluding bracket) - 0.71 lbs (320 g);

Light including batteries and bracket - 0.90 lbs (406 g)

• Flash Rate: 50-70 flashes per minute

- Flash Light Intensity : Minimum of 3 candelas per flash in all directions of upper hemisphere
- Battery: 2 x 1.5 Volt, AA Lithium Batteries (L91) / User replaceable

• Bulb: Ultra-Bright LED

- Operation : Throw overboard or turn upright and strobe light will activate
- Operational Life: 40 hours over 3 cd at 30°C (86°F);
 24 hours over 3 cd at -1°C (30°F)

The light is supplied with a clamp for fastening closed to the lifebuoy.

Tests Carried Out

Evaluation and Test Report edit by Wuhan Testing Center of Marine Life-saving Appliances according to IMO Res. MSC.81(70) as amended by Res.MSC.200(80), MSC.226(82) and MSC.323(89) and filed by RINA with No.: SHFP-13465.

Certification Test Report (Ref No.: 21302-1), issued by IMANNA Laboratory, Inc., according to 46 CRF 161.110 and filed by RINA with No.: SHFP-13919.

Field of Application

Lifebuoy self-igniting light is designed in compliance with MSC.48(66) (LSA Code) with a maximum drop height of 30 m.

Reference Documents

Technical drawings and manuals approved and filed by RINA listed on Approval letter No. : SHFP/2019/00360/XZO01.

Note

Previous MED Module B certificate No.: MED091219WS is annulled and replaced accordingly.

RINA Services S.p.A. Via Corsica, 12 - 16128 Genova Tel +39 010 53851 Fax +39 010 5351000




W S



ATTACHMENT TO CERTIFICATE No. MED171319WS

Page 2 of 2

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production control phase module (D, E or F) of Annex II of the Directive is fully complied with a written inspection agreement with a Notified Body



XXXX/YYYY

"WHEELMARK FORMAT"

XXXX

Notified Body number undertaking surveillance module

YYYY

The year in which the mark is affixed

USCG Approval

This product has been assigned a U.S. Coast Guard module B number (*USCG number:* 161.110/EC0474) to note type approval to Module B only as it pertains to obtaining U.S. Coast Guard approval as allowed by the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment" signed February 27th, 2004.

The manufacturer is allowed to affix the U.S. Coast Guard approval number to the above equipment subject to the authorization of the Notified Body undertaking the surveillance module.

General conditions for the approval

- a) The initial conditions verified by RINA at the time of the approval are to be maintained
- b) Any changes to the initial conditions are to be promptly communicated to RINA, which reserves the right to repeat the relevant assessment
- c) This certificate will no be valid if the manufacturer makes any changes or modifications to the approved equipment, which have not been notified to, and agreed with RINA
- d) RINA personnel are to be allowed to witness during the performances of activities, upon their request
- e) The activities are to be carried out in compliance with the RINA Rules and/or other applicable Rules
- f) Should the specified regulations or standards be amended during the validity of this certificate, the product is to be reapproved prior to it being placed on board vessels to which the amended regulations or standards apply.

Hai Wen Zhang